

STABURAGS NBU 4, 12

Lubricating greases with excellent wear resistance



Benefits for your application

- **Good corrosion protection**
- **Good resistance to ambient media**
- **Excellent wear protection**
- **Good resistance to tribo-corrosion**
- **Good load-carrying capacity**
- **Good sealing effect**

Description

STABURAGS NBU 4, 12 are lubricating greases based on mineral oil and barium complex soap. These products are resistant to very high specific surface pressure, thus ensuring good wear protection. In addition, they are resistant to corrosion, water and many diluted alkaline and acid solutions

It is used on water pumps, wheel bearings and motors; and in the textile industry, on all wet processing equipment such as washing, mercerising and dyeing machines.

Application

STABURAGS NBU 4 has been used successfully on high-speed rolling bearings exposed to humidity or ambient media. It is suitable for rolls, spindles, cam rollers, tensioning rollers and motors.

Application notes

These greases are applied by brush, spatula or conventional metering systems.

STABURAGS NBU 12 is efficient on medium-speed rolling bearings subject to humidity or ambient media.

Material safety data sheets


Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	STABURAGS NBU 4	STABURAGS NBU 12
Cartridge 400 g	+	+
Can 1 kg	+	+
Drum 180 kg	+	+

STABURAGS NBU 4, 12

Lubricating greases with excellent wear resistance

Product data	STABURAGS NBU 4	STABURAGS NBU 12
Article number	017050	017052
NSF-H2 registration		135 689
Chemical composition, type of oil	mineral oil	mineral oil
Chemical composition, thickener	barium complex soap	barium complex soap
Lower service temperature	-20 °C / -4 °F	-15 °C / 5 °F
Upper service temperature	90 °C / 194 °F	130 °C / 266 °F
Service temperature, upper limiting value for continuous lubrication	130 °C	
Colour space	beige	brown
Density at 20 °C	approx. 0.96 g/cm ³	approx. 0.99 g/cm ³
Worked penetration, DIN ISO 2137, 25 °C, lower limit value	245 x 0.1 mm	245 x 0.1 mm
Worked penetration, DIN ISO 2137, 25 °C, upper limit value	275 x 0.1 mm	275 x 0.1 mm
Shear viscosity at 25 °C, shear rate 300 s ⁻¹ , equipment: rotational viscometer, lower limit value	6 000 mPas	9 000 mPas
Shear viscosity at 25 °C, shear rate 300 s ⁻¹ , equipment: rotational viscometer, upper limit value	10 000 mPas	15 000 mPas
Kinematic viscosity of the base oil, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C	approx. 46 mm ² /s	approx. 220 mm ² /s
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 100 °C	approx. 7 mm ² /s	approx. 19 mm ² /s
Drop point, DIN ISO 2176	>= 220 °C	>= 220 °C
Four-ball tester, welding load, DIN 51350 pt. 04	>= 3 000	>= 3 000
Speed factor (n x dm)	500 000 mm/min	approx. 350 000 mm/min
Water resistance, DIN 51807 pt. 01, 3 h/90 °C, rating	<= 1 - 90	<= 1 - 90
Flow pressure of lubricating greases, DIN 51805, test temperature: -15 °C		<= 1 600 mbar
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	60 months	60 months





STABURAGS NBU 4, 12

Lubricating greases with excellent wear resistance



Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

**Klüber Lubrication München SE & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.**

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.



a company of the Freudenberg Group